

SYSTEM TECHNOLOGY

High-efficiency waste heat units and SPI accessories

High-efficiency AHT waste heat units

With the SPI versions of the AHT refrigerated cabinets, you can integrate these into your cooling and heating system. Connection of the SPI refrigerated cabinets to a waste heat unit allows the waste heat to be dissipated directly. As a full-range supplier, we have the right waste heat units for your requirements in our product portfolio. Our sales staff will be happy to inform you in detail about all the possibilities.

The units can be finished with an aluminium, epoxy or KTL coating. With our waste heat units, we cover the performance spectrum from 20 kW to 170 kW per circuit.

AWE

Waste heat unit with pump station, including preparation for waste heat recovery



The waste heat units are available with different sound pressure levels (dB).

PUMP STATION & RECOOLER

Floor, wall, table, or radial installation



Pump station for indoor installation with recooler for outdoor installation



Pump station for outdoor installation

FLOOR INSTALLATION RKBNA 80 kW (up to 170 kW available)



The recoolers are available with different sound pressure levels (dB).





The recoolers are available with different sound pressure levels (dB).

Installation

AHT project management is at your side during the planning, organisation and implementation of the installation. We accompany you step-by-step through your project and support you with our extensive know-how and experience.



SYSTEM TECHNOLOGY ACCESSORIES

Maintenance platform, glycol drip tray, repair switch and other accessories are available on request.



AHT Cooling Systems GmbH

Werksgasse 57 8786 Rottenmann | Austria p. +43 3614 24 51-0 sales@aht.at www.aht.at