



Versatile and seductive

RIO models are the perfect choice for selling ice cream in various places. The broad variety of sizes ensure perfect integration in any store layout and boost your sales.



VISUAL MERCHANDISE

RIO is displaying the goods perfectly to customers due to its low height it can easily be looked into. The smooth-running, two-part, straight sliding glass lid with the proven, patented, sprayed one-piece AHT cover frame ensures easy goods removal. The brilliant LED interior lighting presents your goods in best conditions.



HIGH ENERGY SAVINGS

RIO scores with low energy consumption through reinforced insulation (72 mm). In addition the new optimized fan allows 0.5 kWh energy saving per day.



ENVIRONMENT AND CLIMATE

RIO is completely free of CFCs and HFCs and runs with the ecologically harmless and natural refrigerant propane (R290). R290 has one of the lowest GWPs (global warming potential) on the market.



LOW COSTS

The proven AHT quality guarantees you a trouble-free longevity. RIO is suitable for climate class 3 to 7 by different design variants. RIO is delivered in a robust packaging accessible for forklifts.



SMART INSTALLATION

Thanks to the plug-in installation, RIO is immediately ready for use. With RIO you get a team player who also works with other AHT cooling and freezing units.



MULTIFUNCTIONAL PURPOSE

With the same hight and depth RIO is available in different lenghts. The inner container of white pre-painted and galvanized sheet metal harmonizes with the one-piece plastic frame perfectly. RIO specially scores with the adjustable thermostat and the outer skin condenser. Pollution and maintenance is therefore a thing of the past.

INDIVIDUELLES BRANDING

AHT cooling units are constructed individually: Using our template, you create the design, then we apply it directly during production. ٦į٠

TEMPERATURE RANGES

Freezing
Scooping ice cream

-14°C to -23°C -6°C to -23°C

USPs

OPTIMIZED GOODS REMOVEL

Due to the reduced height ice cream is easily accessible. The glass sliding lids are opening and closing smoothly.

INDEPENDENT POSITIONING

RIO can be served from both sides and is the ideal solution for every area because of different size variants.













RIO H 175


ACCESSORIES


- _ Temperature display: outer (front wall) and/or indoor thermometer
- _ Condensate drain
- _ robust castors (can be braked)
- $_$ Interior light / LED light for RIO S
- _ Light canopy
- _ Energy-saving fan
- _ Insulation cover for horizontal RIO chests

- $_$ baskets and dividers
- _ Lock for sliding covers
- _ Additional mounting options in the form of rivet nuts
- $_$ Frame heating for RIO S

RIO S

68 / 100 / 125 / 150 /175







DIMENSIONS

RIO S				68		100		125		150	175
lenght, exterior / interior		mm		680 / 530		1,000 / 850		1,250 / 1,100		1,500 / 1,350	1,750 / 1,600
depth, exterior / interior		mm		650 / 500		650 / 500		650 / 500		650 / 500	650 / 500
height outside front / rear	-	mm	-	769 / 883	-	769 / 883	-	769 / 883	1	769 / 883	769 / 883
stacking height front / rear		mm	1	530 / 570		530 / 570		530 / 570		530 / 570	530 / 570

RIO H

68 / 100 / 125 / 150 /175





■ DIMENSIONS

RIO H				68	100	125		150		175
lenght, exterior / interior		mm		680 / 530	1,000 / 850	1,250 / 1,100		1,500 / 1,350		1,750 / 1,600
depth, exterior / interior		mm		650 / 500	650 / 500	650 / 500		650 / 500		650 / 500
height outside front / rear		mm		883 / 883	883 / 883	883 / 883		883 / 883		883 / 883
Stacking height	Ī	mm		610	610	610		610	Ī	610



AHT Cooling Systems GmbH

Werksgasse 57 8786 Rottenmann | Austria p. +43 3614 24 51-0 sales@aht.at www.aht.at